


Barrier Free, Roll In Shower 50" x 50" **Ella Freedom** - Center Drain



Model#

5050 BF 4P 1.0C-WH FRDM 5050 BF 4P 1.0C-BN FRDM 5050 BF 4P 1.0C-B FRDM

Ella Freedom Accessories (page 2):



The Perfect Fall Prevention System

Outside Dimensions: 50.25" W x 50.125" L x 77.75" H

Shipping Dimensions: 60" W x 48" L x 72" H Shipping Weight: 439 lbs.

Net Weight: 426 lbs.

Threshold Height: 1" Change of Level L

Package Options:

- White (W), Bone (BN) or Biscuit (B) Shower Panels
- Standard, Plus 24, Plus 36, Freedom, Deluxe, or Elite (premium fixtures in white, brilliant or satin)
- Flange Trim Molding Kit
- Multi-Piece Window Trim Kit

Panels:

Features:

- Premium marine grade gel-coat, four piece shower with 8" classic tile pattern
- Wood and steel reinforced walls for placing grab bars and seats anywhere (not dependent on stud locations)
- Easy shower wall assembly pin-lock system allowing front side installation
- Precision fit wall panel seams (match into grout pattern)
- Grip-Sure[™] floor texture
- Molded soap ledges
- Self supporting, pre-leveled shower base (no mudset required)
- Shower door friendly (squared corners allow door installation)
- Ships pre-assembled, heavy duty crating protects product in transit

Accessories:

- [1] Three (3) 16" Polished Chrome Finish Curved Grab Bars
- [2] One (1) 2-in-1 Bar for Shower Valve
- [3] 2" Chrome strainer brass drain with friction seal
- [4] Collapsible Dam Kit

Codes:

IPC, UPC, ANSI Z 124.2, NAHB, HUD, FHA

Warranty:

30 Year Limited Lifetime Warranty (on shower panels)*

*For more information please visit www.ellasbubbles.com

L Change of Level threshold has manageable 1/4" vertical rise to easily coordinate with minimum finished flooring.




Barrier Free, Roll In Shower 50" x 50" **Ella Freedom** Accessories





Barrier Free, Roll In Shower 50" x 50" 5050 BF 4P 1.0 - Center Drain





Barrier Free, Roll In Shower Features

STRENGTH Wood & Steel Reinforced Walls All wall panels Metal conduit around the are backed perimeter for unmatched with 3/8" wood strength accessories can be installed Fiberglass resin structural anywhere, substrate cures to a seamless any time strong encasement Premium Marine-grade Polyurethane Gel-coat fiberglass surface reinforcement for beautiful, long-lasting machined to a shower surface flush, level surface High density


Twice the weight and twice the raw materials used in the construction of our showers than listed by any of our competitors.

Wood reinforced core walls and high density base. Metal conduit around perimeter of EACH panel for added strength.

ADAPTABILITY

Customized Accessory Placement

The wood reinforced core walls allow the fixtures to be installed right onto the wall studs by eliminating the need for a drywall backing.



SHOWER DOOR FRIENDLY

Your choice: Curtain or Door

Square corners in Ella shower construction allow for framed or frameless shower doors to be installed.




Image for Illustration only

FRONT SIDE INSTALLATION

Aluminum Pin and Slot System for a contractor friendly front side installation.

An installation may be finished in a fraction of the time. No more need to get behind the panels to bolt large panels together.







structural foam



AVAILABILITY

Your Project won't be held up

Ella showers are manufactured, inspected and shipped directly from the factory within 5 - 7 business days.

Rush orders are available upon request (white only).

No order is too big or small.

SMART PACKINGMulti-piece Shower in a Box



In stock for Rapid Ship

